

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 98 953 - 97 HH

Company Rich. Klinger Dichtungstechnik GmbH & Co. KG
Am Kanal 8-10
2352 Gumpoldskirchen, AUSTRIA

Product Description FLAT GASKETS

Type KLINGERSIL C-4430 / 4433 / 4409 / 44XL

Environmental Category None

Technical Data / TECHNICAL DATA (continued)

Range of Application

Type	KLINGERSIL C-4430
Density	1.75 [g/cm ³]
Compressibility	9% { ASTM F 36 J }
Recovery	=/ > 50% { ASTM F 36 J }
Tightness	< 1.0 [ml/min] { DIN 3535-6 }
Soluble chloride content	150 [ppm]
Klinger cold / hot compression, 50 MPa	thickness decrease at 23 [°C]: 8% thickness decrease at 300 [°C]: 11%

RANGE OF APPLICATION

The gaskets may be used under consideration of the mechanical and physical properties as well as the chemical resistance as follows:

- Ship's piping systems excluding cargo lines on Chemical and Gas Tankers carrying propylene oxide and mixtures of ethylene / propylene oxide.
- Maximum allowable working pressure and temperature according to the specification of the manufacturer.

Test Standard • ASTM and DIN

Documents • Test Reports
• Technical Data
• Audit Report

Remarks • None

Valid until 2013-11-20

Page 1 of 2

File No. II.C.09

Hamburg, 2008-11-20

Type Approval Symbol



Germanischer Lloyd

Hanspeter Raschle
Hanspeter Raschle

Peter Gierhan
Peter Gierhan

This certificate is issued on the basis of "Guidelines for the Performance of Type Approvals Part 1, Procedure".

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 98 953 - 97 HH

TECHNICAL DATA

Type	KLINGERSIL C-4433
Density	1.8 [g/cm ³]
Compressibility	7% { ASTM F 36 J }
Recovery	=/≥ 60% { ASTM F 36 J }
Tightness	0.2 [ml/min] { DIN 3535-6 }
Soluble chloride content	150 [ppm]
Klinger cold / hot compression, 50 MPa	thickness decrease at 23 [°C]: 7% thickness decrease at 300 [°C]: 8%

Type	KLINGERSIL C-4409
Density	2.0 [g/cm ³]
Compressibility	7% { ASTM F 36 J }
Recovery	=/≥ 50% { ASTM F 36 J }
Tightness	0.2 [ml/min] { DIN 3535-6 }
Soluble chloride content	150 [ppm]
Klinger cold / hot compression, 50 MPa	thickness decrease at 23 [°C]: 10% thickness decrease at 300 [°C]: 10%

Type	KLINGERSIL C-44XL
Density	1.6 [g/cm ³]
Compressibility	10% { ASTM F 36 J }
Recovery	=/≥ 55% { ASTM F 36 J }
Klinger cold / hot compression, 50 MPa	thickness decrease at 23 [°C]: 12% thickness decrease at 300 [°C]: 19%

The selection of the gaskets for the corresponding application and the appropriate installation is to be in acc. with the instructions of the manufacturer.

Valid until 2013-11-20

Page 2 of 2

File No. II.C.09

Hamburg, 2008-11-20

Type Approval Symbol



Germanischer Lloyd

i.v. Hanspeter Raschle
Hanspeter Raschle

i.A. P. Gierman
Peter Gierman

This certificate is issued on the basis of "Guidelines for the Performance of Type Approvals Part 1, Procedure".